

Name Ashford Formula



Product ID Classification 03 35 00.00 Concrete (footing):  
Concrete Finishing

Website www.ashfordformula.com

Manufacturer Curecrete Distribution, Inc. Contact Name Jerald Jones  
Address 1203 West Springcreek Place Title President  
Springville, UT 84663 Phone 8017873799  
USA Email jerry@ashfordformula.com

Description Ashford Formula is a zero VOC, chemically reactive concrete sealer, hardener and dustproof. This deep penetrating sealer chemically reacts with the concrete forming a crystalline structure within the concrete pore, filling the pore, and solidifying the concrete into a densified mass.

This reaction chemically hardenes the concrete surface, rendering it abrasion resistant, dustfree and resistant to the penetration of surface contaminants. The results are permanant. No retreatment is required. Ashford Formula does not contribute to Alkali Silicate Reaction (ASR).

The chemical identity of the proprietary components have been withheld to preserve the intellectual property rights of Curecrete Distribution, Inc. However, the full CAS numbers have been entered into the HPD database which is verified by the WECRS Green tool. The quantity of each proprietary chemical falls below the required reporting threshold for the HPD Collaborative. The product as a whole is nontoxic and the hazardous properties of the proprietary chemicals are undetectable and not relevant to the product as supplied or used. All chemical hazards are listed and have been disclosed.

Release Date 2016-05-23  Self-declared  
Expiry Date 2019-05-23  Second Party Certifier  
HPD URL <https://builder.hpd-collaborative.org/uploads/files/hpds/1242/3220-20160523151332.pdf>  Third Party Certificate #

## SUMMARY DISCLOSURE

The content of this product was assessed for health hazard warnings as required using Pharos

Residuals Disclosure  Measured 100 ppm (ideal)  Measured 1000 ppm  Predicted by process chemistry  As per MSDS (1,000 & 10,000 ppm)  Not disclosed  Other

Full Disclosure of Intentional Ingredients  Yes  No  
Full Disclosure of Known Hazards  Yes  No

Disclosure Notes  
No known residuals exist from the manufacturing of this product or based on the Chemical Suppliers MSDS sheets.

## Contents in Descending Order of Quantity

WATER , SODIUM SILICATE , Sodium metasilicate nonahydrate , Undisclosed (Tracer) , Undisclosed (Reagent) , Undisclosed (Proprietary Catalyst)

Hazards  PBT (Persistent Bioaccumulative Toxic)  Cancer  Gene Mutation  Development  Reproductive  Endocrine  Respiratory

Highest concern GreenScreen score - List Translator Possible Benchmark 1  Neurotoxicity  Mammal  Skin or Eye  Aquatic toxicity  Land toxicity  Physical hazard  Global warming  Ozone depletion  Multiple  Unknown

Total VOC Content Material (g/L) Regulatory (g/L) 0.00 Does the product contain exempt VOCs?  N/A  Yes  No Are there VOC-free tints available?  N/A  Yes  No

Notes  
Ashford Formula is a waterbased product containing no VOC's

**Certifications + Compliance**

**VOC Emissions**

Not tested

**Flame Retardants**

EU Classification of the reaction to fire performance of construction products - Euroclass E

**VOC Content**

Not tested

**Flame Retardants**

EU Classification of the reaction to fire performance of construction products - Euroclass E

The HPD Standard is solely a declaration of product content and direct health hazards associated with exposure to its individual contents. It is not a full assessment of environmental impacts from the life cycle of this product. It is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

This Health Product Declaration was generated following the requirements of the noted Standard version and is valid for a total of three years after date of issue or three months after a substantive change of product contents occurs. Users should verify that this Health Product Declaration is compliant with the most current version of the HPD Standard. Accuracy of claims made in this Health Product Declaration is the sole responsibility of the listed manufacturer and certifier (if applicable). The HPD Collaborative does not warrant any claim made herein, explicit or implicit. The HPD Standard is an “open standard” developed and managed by the HPD Collaborative, a nonprofit organization. For more information, visit [hpdcollaborative.org](http://hpdcollaborative.org).

## CONTENT IN DESCENDING ORDER OF QUANTITY

All ingredients must be assessed for health warnings against Priority Hazard Lists, regardless of disclosure level.

Priority Hazard Lists and information on the GreenScreen Benchmarks can be found at [www.hpdcollaborative.org/hazardlists](http://www.hpdcollaborative.org/hazardlists).

**GS:** GreenScreen Benchmark; **RC:** Recycled Content, **PC:** Post Consumer, **PI:** Post Industrial (Pre-consumer), **BO:** Both; **Nano:** comprised of nanoscale particles or nanotechnology

Name	CAS RN	% weight	GS	RC	Nano	Role
<b>Hazard A</b>	<b>Warning A</b>					
<b>Hazard B</b>	<b>Warning B</b>					
<b>Hazard C</b>	<b>Warning C</b>					
<b>Hazard D</b>	<b>Warning D</b>					
<b>Hazard E</b>	<b>Warning E</b>					
<b>Notes</b>						
<b>WATER</b>	7732-18-5	45 - 70 %	4	N	N	Carrier
None found	No warnings found on HPD Priority lists					
Water: Carrier						
<b>SODIUM SILICATE</b>	1344-09-8	15 - 35 %	LT-U	U	N	Reactive Concrete Modifier
None found	No warnings found on HPD Priority lists					
Reactive Concrete Modifier						
<b>Sodium metasilicate nonahydrate</b>	13517-24-3	1 - 13.5 %	LT-U	U	N	Reactive Concrete Modifier
None found	No warnings found on HPD Priority lists					
Reactive Concrete Modifier						
<b>Undisclosed (Tracer)</b>	Undisclosed	0.05 %	LT-U	N	U	Tracer
None found	No warnings found on HPD Priority lists					
Verify authenticity of product						
<b>Undisclosed (Reagent)</b>	Unknown	0 - 0.05 %	LT-U	U	U	Undisclosed Reagent
MAMMALIAN	EU R-Phrases: R25: Toxic if swallowed.					
SKIN IRRITATION	EU H-Statements: H315 Causes skin irritation					
0-0.05% The chemical identity has been withheld to preserve the intellectual proprietary rights of Curecrete Distribution, Inc However we have verified the chemicals with the HPD Database which is verified by the WECRS Green Tool. The quantities of chemical falls below the required reporting threshold for the HPD Collaborative. The product as a whole is non-corrosive and the hazardous properties of this chemical is undetectable and not						

relevant to the product as supplied or used.

<b>Undisclosed (Proprietary Catalyst)</b>	Undisclosed	0 - 0.01 %	LT-P1	U	U	Proprietary Catalyst
MAMMALIAN	EU R-Phrases: R25: Toxic if swallowed.					
SKIN IRRITATION	EU H-Statements: H314 Causes severe skin burns and eye damage					
MULTIPLE	VwVwS: Class 2 Hazard to Waters					
0-0.005% The chemical identity has been withheld to preserve the intellectual proprietary rights of Curecrete Distribution, Inc However we have verified the chemicals with the HPD Database which is verified by the WECRS Green Tool. The quantities of chemical falls below the required reporting threshold for the HPD Collaborative. The product as a whole is non-corrosive and the hazardous properties of this chemical is undetectable and not relevant to the product as supplied or used.						

**CERTIFICATIONS AND COMPLIANCE**

**Certifying Party** = First: Manufacturer’s self-declaration; Second: Verification by trade association or other interested party; Third: Verification by independent certifier (ideal).

**Applicable facilities** = Manufacturing sites to which testing applies.

Type	Standard or Certification			Certifier or Laboratory
	Certifying Party	Issue Date	Expiry Date	Certificate URL
	<b>Applicable Facilities</b>			
	<b>Notes</b>			
VOC Emissions	N/A			
VOC Content	Not tested			
Recycled Content	Not tested			
Flame Retardants	EU Classification of the reaction to fire performance of construction products - Euroclass E			European Commission
	Government enforced claim	2007-07-01		<a href="https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1430251139.pdf">https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1430251139.pdf</a>
	ALL			
	ntended uses: for the protection of concrete structures – Impregnation • Ingress protection (1.2) • Physical resistance (5.2) Is in compliance with the EU Construction Products directive (89/1060EEC) and meets the requirements of EN 1504-2 for the intended uses indicated herein: Declared characteristics Test method Declared characteristics Abrasion resistance (Böhme test) EN 13892-3 At least 30% improvement in abrasion resistance in comparison with a non-impregnated sample Capillary absorption and permeability of water En 1062-3 ≤0.1kg/m2 xh0.5 Depth of penetration EN 1504-2 ≥ 5mm Impact resistance EN ISO 6272-1 Class 2: ≥ 10 Nm Adhesion			

strength by pull off test EN 1542 - vertical  $\geq 0.8$  MPa - horizontal without trafficking  $\geq 1.0$  MPa - horizontal with trafficking  $\geq 1.5$  MPa

Flame Retardants	EU Classification of the reaction to fire performance of construction products - Euroclass E		European Commission
	Government enforced claim	2007-07-01	<a href="https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1430251139.pdf">https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1430251139.pdf</a>
ALL			
ntended uses: for the protection of concrete structures – Impregnation • Ingress protection (1.2) • Physical resistance (5.2) Is in compliance with the EU Construction Products directive (89/1060EEC) and meets the requirements of EN 1504-2 for the intended uses indicated herein: Declared characteristics Test method Declared characteristics Abrasion resistance (Böhme test) EN 13892-3 At least 30% improvement in abrasion resistance in comparison with a non-impregnated sample Capillary absorption and permeability of water En 1062-3 $\leq 0.1$ kg/m <sup>2</sup> xh0.5 Depth of penetration EN 1504-2 $\geq 5$ mm Impact resistance EN ISO 6272-1 Class 2: $\geq 10$ Nm Adhesion strength by pull off test EN 1542 - vertical $\geq 0.8$ MPa - horizontal without trafficking $\geq 1.0$ MPa - horizontal with trafficking $\geq 1.5$ MPa			
		2011-03-18	2021-03-18
			<a href="https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1439399062.pdf">https://builder.hpd-collaborative.org/uploads/files/certifications/1242/1439399062.pdf</a>
ALL			
VOC Certification			

**ACCESSORY MATERIALS**

This section is for additional products required by warranty or recommended by the manufacturer for installation (such as adhesives, fasteners, or factory coatings) or for maintenance, cleaning, or operations. Refer to Health Product Declarations, published separately, for a complete view of these products.

Note: This declaration is not intended to address hazards of the installation process.

Required or Recommended Product	URL for Companion Health Product Declaration
<b>Condition when required or recommended and/or other notes</b>	

**NOTES**