



Product Description

Revolutionary, Cutting Edge Technology

CreteClean Plus with Scar Guard™ is uniquely formulated to clean and condition densified and densified-polished concrete. Proprietary polar technology pulls contaminants out and up from concrete and holds it in suspension, providing maximum cleaning efficiency.

Reduced Environmental Impact

CreteClean Plus with Scar Guard™ is a water-based detergent that contains no Volatile Organic Compounds (VOCs). Due to its high concentration, less product is required for use, and therefore less needs to be purchased, shipped, and stored, greatly reducing its overall environmental impact.

Improves Floor Performance

The chemically advanced technology of CreteClean Plus with Scar Guard™ elevates it from a detergent to a performance enhancing cleaning agent. Regular and frequent use of CreteClean Plus with Scar Guard can, over time:

- + Help strengthen and harden concrete surfaces,
- + Decrease the visibility of minor scratches and blemishes,
- + Decrease porosity, and
- + Help maintain the sheen of densified concrete surfaces.

Suitable for Use in Food Handling Establishments

CreteClean Plus with Scar Guard™ is approved for use in institutional, industrial and food handling establishments.

Directions for Use

General Cleaning

CreteClean Plus with Scar Guard™ is simple and easy to use. First, remove any debris from the area to be cleaned. CreteClean Plus can then be applied by wet mop*, automatic scrubber or other means. Remove any excess diluted CreteClean Plus and allow the concrete surface to air-dry. For enhanced results on concrete that has been treated with the Ashford Formula™ or RetroPlate® System, periodically burnish or buff the surface with a non-aggressive pad or polishing pad. *To avoid streaking, use only a rayon mop head, and change cleaning solution every 800-1,000 ft² (244-305 m²).

Poultice Cleaning Procedures for Severe Oil Staining

Remove all loose soil and fine grit. Mop down CreteClean Plus diluted at 4 oz / gal of water (31.2-39 mL / L). Agitate the solution to assist the product in penetrating the soil's surface. Cover the wet surface with plastic film and tape down edges. Allow area to remain wet for 10-15 minutes or longer if possible. Remove the plastic film

Technical Info +

Form:	Clear, Green Liquid with Fresh Scent Weighs 8.5 lbs / gal (1.02 kg / L)
Flashpoint:	Not Applicable
Freezing:	If product freezes, agitate to re-emulsify
pH:	11.2 [+/- 0.5] (Concentrate) 8.5 - 8.6 (Diluted for Use)
Packaging:	55 gal (208 L) Drums 5 gal (19 L) Pails
Storage Life:	Two (2) Years
Dilution Ratio:	General Cleaning: 1 oz CreteClean Plus / gal of H ₂ O (7.8 mL / L) Poultice Cleaning: 4 oz CreteClean Plus / gal of H ₂ O (31.2-39 mL / L)

and dispose of soiled solution. The procedure may need to be repeated if soil leaches back to the surface as the concrete completely dries out. **Note: This procedure is designed for spot removal of significant oil or grease staining. It is not a cleaning procedure.**

Special Considerations

Several applications of **CreteClean Plus with Scar Guard™** may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as ***CreteStrip™**, may be necessary.

Additionally, acids, salts, deicers and other harmful substances should be promptly removed to avoid damage to your floor. A proper, regular and frequent maintenance program is highly recommended. Making CreteClean Plus a regular part of your maintenance program will ensure superior results.

*CreteStrip is manufactured exclusively by Curecrete Distribution, Inc. For details visit www.curecrete.com.

Availability & Cost

CreteClean Plus with Scar Guard™ is manufactured exclusively for Curecrete Distribution, Inc. and is distributed through a worldwide network of regional factory warehouses, area sales representatives and distributors. For pricing information, please call **801.489.5663** or toll free at **800.998.5664**.

Extended Manufacturer Warranty

Due to the superior performance achieved by regularly using **CreteClean Plus with Scar Guard™**, concrete surfaces treated with the Ashford Formula™ or RetroPlate® System can qualify for an extension of their original Manufacturer Warranty to a Lifetime Warranty. Qualifying conditions apply. Contact Curecrete Distribution, Inc. for more information.



Extended Manufacturer Warranty (Continued)

Curecrete Distribution, Inc. warrants this product to be free from any manufacturing defects.



Technical Assistance & SDS

Technical Help:

Phone: **801.515-6219**
Free: **844.644.4304**
Email: **cretecleantechnical@curecrete.com**

Emergency:

Phone: **801.629.0667**
Free: **800.633.8253**

Please scan the code for this product's Safety Data Sheet.



Product Distribution & More Information

Curecrete Distribution, Inc.
1203 W. Spring Creek Place
Springville, UT 84663 USA

Phone: 801.489.5663
Free: 800.998.5664
Fax: 801.489.3307

Advanced Floor Products
P.O. Box 80533
Provo, UT 84605 USA

Phone: 801.712.3420
Free: 888.942.3144
Fax: 801.812.3400

Please visit our website, **www.curecrete.com** for information on this and other available products.